

you can
Canon

**imagePRESS
C7000VP/C6000VP**

High Volume Digital
Colour Production

Make the biggest imPRESSion on your business

For the most complex jobs turn to Canon's flagship Digital Colour Production engines. Delivering exceptional quality and maximum productivity across all media types and weights, the imagePRESS C7000VP and imagePRESS C6000VP satisfy your most demanding production requirements.



COLOUR imagePRESS C7000VP/C6000VP

Incredible quality

Vivid colours and outstanding pin-sharp images that look and feel like offset production.

Precision printing

Precision printing with automatic page-by-page image and density controls provide exceptional consistency for true "production safe" colour.

Exceptional consistency

Maximum Productivity

Full production speeds of up to 70 ipm are achieved across all media types and weights up to 300 g/m² for deadline-beating performance.

A sizeable 10,000 sheets paper supply with up to 8 different sources is

complemented by air-assisted feeding for exceptional reliability and over 2 hours of uninterrupted production.

Exceptional reliability

Highly innovative

Canon's V-toner with its ultra-fine particle size and oil-less fusing characteristics combine with enhanced image control technologies to provide gloss optimisation for an optimal finish on all media.

Exceptional finishing

Choose from a huge diversity of in-line finishing possibilities including perfect binding. Intelligent Registration technology ensures impressive results print after print.

Exceptional image quality and productivity.



imagePRESS

Specifications imagePRESS C7000VP / C6000VP

imagePRESS C7000VP MARKING ENGINE Recommended monthly volume C7000VP: 70,000 to 300,000 pages (A4) C6000VP: 50,000 to 250,000 pages (A4) Maximum monthly volume C7000VP: 550,000 pages (A4) C6000VP: 515,000 pages (A4) Resolution Registration tolerance HDD capacity (Scan and Mailbox) Image memory (SDRAM) Media weight Paper deck (Marking Unit) 2 Drawers Paper feeding capacity Paper finishing capacity Dimensions (W x D x H) Weight Power		Paper sizes (POD Decks & Standard Paper Trays) A4, A4R, A3, SRA3, B4, JIS-B5, JIS-B5R, LGL, LTR 13" x 19.2" (330.2 x 487.7mm) 12" x 18" (305 x 457mm) 11" x 17" (279 x 432mm) 4-pane postcard Custom sizes (182 x 182mm to 330 x 487mm) Paper level detection Double feeding detection Escape tray Dimensions (W x D x H) Weight Power		SADDLE FINISHER – AB2 Paper type (booklet making) Paper size (booklet making) Stacking capacity Booklet sheets Dimensions (WxDxH) Weight Power BOOKLET TRIMMER-C1 Type Maximum number of sheets trimmable Possible trimming size Conveyor Capacity Dimensions (W x D x H) Weight Power		64 to 200 g/m ² (inner pages), up to 300 g/m ² (cover) A3, A4R, B4, SRA3, 12"x18", 11" x 17", LGL, LTR 30 booklets (80 g/m ²) 2 to 20-sheets (80 g/m ²) 800 x 792 x 1,180mm 178kg 240V, 8A Leading-edge trimmer with delivery tray 40 sheets (80 g/m ²), 38 sheets (80 g/m ²) + 2 sheets (300 g/m ²) All sizes supported by Saddle Finisher-AB2 30 booklets 1,575 x 792 x 1,040mm 152 Kg 240V, 4A max	
PRODUCTIVITY Size Weight (g/m ²) A4 64 to 300 g/m ² A3 64 to 300 g/m ² SRA3 64 to 300 g/m ² 13x19.2" 64 to 300 g/m ²		C7000VP Simplex Duplex (ppm) (ipm) 70.0 65.4 36.0 36.0 33.6 33.6 31.0 31.0		C6000VP Simplex Duplex (ppm) (ipm) 60.0 60.0 30.8 30.8 28.8 28.8 26.6 26.6			
COLOUR IMAGE READER-H1 (REQUIRES DADF OR PLATEN COVER) Scanning lamp Resolution Scanning speed Dimensions (W x D x H) Weight		Xenon tube (Light intensity: 20,000 lx) 600 x 600dpi 80ipm (300dpi) 50ipm (600dpi) 732 x 595 x 105mm 17.5 Kg					
DADF-R1 Original document size Maximum document weight Tray capacity Document size detection Document process speed (copying) Dimensions (W x D x H) Weight		A4, A3, A5, LGL, LTR, Custom sizes (148 x 210mm to 297 x 420mm) A4, A5: 216 g/m ² (Single-sided / double-sided) A3: 216 g/m ² (Single-sided), 200 g/m ² (Double-sided) 100 sheets (80 g/m ²) Length: photo sensor Width: slide guide 50ipm (single-sided) - A4, 600dpi 25ipm (double-sided) - A4, 600dpi 646 x 570 x 143mm 21.5 Kg					
POD DECK-A1 (PRIMARY POD AND SECONDARY POD) POD Deck-A1 (Primary) 3 Drawers POD Deck-A1 (Secondary) 3 Drawers Pickup method Paper type		4,000 sheets (80 g/m ²) (410mm) total 4,000 sheets (80 g/m ²) (410mm) total Air separation method Thin (64 to 79 g/m ²) Plain (80 to 105 g/m ²) Thick (106 to 300 g/m ²) Recycled (64 to 256 g/m ²) Coloured (64 to 79 g/m ²) 1-side coated (80 to 300 g/m ²) 2-side coated (80 to 300 g/m ²) Embossed paper, (80 to 300 g/m ²) Vellum paper (64 to 300 g/m ²) Bond paper, Punched paper (64 to 105 g/m ²) Tab paper (151 to 209 g/m ²) (A4) Transparency (A4, A4R) Label (A4, A3, B4) Postcard					
HIGH CAPACITY STACKER-C1 Paper type Stacker Dolly (64 to 300 g/m ²) Output tray (64 to 300g/m ²) Downstream output (64 to 300g/m ²) Tray capacity Stack tray Output tray Dimensions (W x D x H) Weight Power One stacker unit Two stacker units		A4, A3, SRA3, B4, 11"x17", 12"x18", 13"x19.2" Tab Paper (A4, LTR), Custom size (216 x 182mm to 330 x 487mm) A4, A4R, A3, SRA3, B4, 11"x17", 12"x18", 13"x19.2" Tab Paper (A4, LTR), Custom size (182 x 182mm to 330 x 487mm) A4, A4R, A3, SRA3, B4, 11"x17", 12"x18", 13"x19.2" Tab Paper (A4, LTR), Custom size (182 x 182mm to 330 x 487mm) 5,000 sheets (80 g/m ²) (570mm) 1,000 sheets (80 g/m ²) (100mm) 860 x 765 x 1,290mm 200 Kg 240V, 300W 240V, 600W					
PERFECT BINDER Bookbinding Method Bookbinding Thickness Book Size Margin Trimming Insertion Unit Capacity Cover Size Paper Weights Power Source Dimensions (H x W x D) Weight		Hot Glue Spine with Wraparound Cover Approx. 10 to 200 sheets (1mm to 25mm) SRA4 (Maximum Before Trimming) Integral trimming device - 3 Sides, 1 side or no trimming Upper Tray: 200 sheets (A4 80 g/m ²) Lower Tray: 200 sheets (13"x19.2" 80 g/m ²) Up to 13" x 19.2" 64 - 163 g/m ² (Insertion sheets) 64 - 300 g/m ² (Cover sheets) 240V, 10A 1360mm x 920mm x 783mm Approximately 324 Kg					
FINISHER-AB1 Paper Weight Paper Size Paper size (staple) Stacking capacity (Non-stapled) Tray A Tray B Stacking capacity (Stapled) Tray A Tray B Staple capacity A4, A4R, B4, B5 A3 Staple cut Dimensions (W x D x H) Weight Power		64 to 300 g/m ² As supported by Marking Engine A4, A4R, A3, B4, JIS-B5 3,000 sheets 2,000 sheets 100 sets 100 sets 100 sheets (80 g/m ²) max 50 sheets (80 g/m ²) max Staple cut for small staple jobs 800 x 792 x 1,180mm 126 Kg 240V, 250W max					
EYE-ONE PROCESS CONTROL – PRODUCTION Colour libraries included Printer verification Package contents		PANTONE® color bridge EC PANTONE® solid coated PANTONE® solid matte PANTONE® uncoated Fogra27 Fogra39 Canon verification Eye-One Pro Spectrophotometer iO Table Measurement accessories Carrying Case Eye-One Process Control CD					

Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change. ® and ©: All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

you can
Canon

Canon Inc.
www.canon.com

Canon Europa N.V.
www.canon-europe.com

English Edition
© Canon Europa N.V., 2008 (04/08)



Canon's GENUINE logo means quality all-round performance

